

**Bamboo Hues** vol.2

**Strand Woven Natural**

**Technical Specifications**

<p><b>Description:</b></p> <p><b>Warranty:</b></p> <p><b>Species:</b></p> <p><b>Installation:</b></p> <p><b>Sizes:</b></p> <p><b>Thickness:</b></p> <p><b>Finish:</b></p> <p><b>Colors</b></p> <p><b>Strand Woven pressed:</b></p> <p><b>VOC Emissions:</b></p> <p><b>Abrasion Resistance:</b></p> <p><b>Density Impact:</b></p> <p>[ASTM 1037]</p> <p><b>Compression Strength:</b></p> <p>[ASTM 3501-86A]</p> <p><b>Dimensional Tolerance:</b></p> <p><b>Slip Resistance:</b></p> <p><b>Moisture Content:</b></p> <p><b>Certified Manufacturing:</b></p> <p><b>Green Build Statement:</b></p>	<p>Solid strand woven bamboo infused with cork flooring (compressed bamboo)</p> <p>15-year Class 34 – Lifetime structural</p> <p>Mao Tzu Moso6™ Bamboo and quercus suber</p> <p>Glue-down</p> <p>approx. 5 5/8" X 72"</p> <p>Micro-beveled edge – slight .2mm eased edge</p> <p>12.7 mm</p> <p>Endura AR+ commercial acrylic finish with nano ceramic particulates</p> <p>Solvent free, 100% solid, Non-off gassing</p> <p>36 standard prefinished colorways – Custom colors available</p> <p>Cold Pressed at 2000 US tons</p> <p>Proprietary phenol resin adhesive used in manufacturing, the formaldehyde emission exceeds E0 standard, no urea formaldehyde, no halogenated hydrocarbons, herbicides, heavy metals and any harmful emissions</p> <p>800 revolutions</p> <p>Brinell rating of 14.3</p> <p>Janka test data +2700</p> <p>5,000-psi avg</p> <p>.0075% l                      N/A w</p> <p>[ASTM D 2394]                ADA and OSHA compliant</p> <p>&gt; 6 to &lt; 9% [ASTM D 4442]</p> <p>ISO 9001</p> <p>CARB2012</p> <p>Lacey Act Compliance</p> <p>Natural Bamboo floors contribute to satisfying LEED credits for Rapidly Renewable Resources [MR] and Low Emitting Materials [EQ] under the LEED Rating System. The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes. Natural Bamboo® Strand Woven Solid can also contribute to attaining points within the Environmental Quality section of the LEED Rating Systems as it uses adhesives that meet the SCAQMD rule #1168 and it contains no added urea-formaldehyde, as required by LEED. The LEED (Leadership in Energy and Environmental Design) Green Building Rating System is the nationally accepted benchmark for the design, construction, and operation of high performance green buildings as administered by U.S. Green Building Council. USFloors is a member of the USGBC.</p>
--	--