

## Architectural Specification

CSI SECTION 09 62 23

### PREFINISHED SOLID T/G BAMBOO FLOORING with ENDURA AR+™

#### PART ONE- GENERAL

##### 1.01 QUALITY ASSURANCE

###### A. Qualifications:

###### 1. Manufacturer Qualifications:

- a. Use low-VOC and EØ compliant adhesives and finishes in manufacturing of all products.
- b. Minimum five years experience in manufacturing and distributing bamboo flooring of the type specified.
- c. Member: National Wood Flooring Association, United States Green Building Council

###### 2. Installer Qualifications:

- a. Minimum three years experience in hardwood flooring installation.
- b. Minimum three years experience in installation of hardwood flooring over radiant heating systems.

##### 1.02 DELIVERY, STORAGE, AND HANDLING

- ###### A. Deliver flooring to project site in original boxes no less than 72 hours prior to start of installation open cartons to acclimate.

##### 1.03 PROJECT/SITE CONDITIONS

- ###### A. Environmental Requirements: Installation spaces, flooring and adhesive must be maintained at normal occupancy temperature and humidity levels (HVAC working) for minimum 3 days prior to installation. Installation contractor must test for moisture, as referenced in the installation guidelines, ensuring that moisture content of product relative to subfloor is sufficient for installation (less than 3% moisture content difference between the material and the subfloor installed).

##### 1.04 WARRANTY

- ###### A. Commercial: 10 Year commercial warranty warrants the finish not to wear through under normal light commercial use for a period of 5 years. (Gloss reduction or surface scratches are not considered surface wear.) Remediate a dull finish with spot or overall recoating care systems. This warranty pertains to the terms and conditions of the manufacturer referenced for aluminum oxide finished floors.
- ###### B. Limited lifetime Structural Warranty: USFloors bamboo flooring warrants to the original purchaser to be free from defects in manufacturing for the useable lifetime of the product. This covers the bonding agent process that includes the separation of the bamboo-to-bamboo construction that each bamboo board incorporates. In the event of a defect, USFloors will arrange for a credit based on the original purchase of the product.
- ###### C. Limited lifetime Residential Wear: USFloors bamboo flooring warrants to the original owner to be free from defects in manufacturing from the purchase date. This covers the surface structure that each USFloors bamboo board incorporates. In the event of a defect, USFloors will arrange for a credit based on the original purchase.

#### PART TWO- PRODUCT

##### 2.01 MANUFACTURER

USFloors Inc.  
3580 Corporate Drive  
Dalton, GA 30721 USA  
800.404.2675 X28  
[www.USFloorsllc.com](http://www.USFloorsllc.com)

##### 2.02 MATERIALS

- ###### A. Bamboo Flooring: USF Contract Natural Bamboo® Prefinished T/G with ENDURA AR+™
1. Species: Mao Tzu – Moso6™ Bamboo
  2. Size: 37 ¾" x 3 ¾" x 5/8" and 75 ½" x 3 ¾" x 5/8"
  3. Edge: Tongue and groove with micro-bevel edge channeled backing
  4. Chemical Treatment: Natural borate solution and hydrogen peroxide to eliminate pests and mildew
  5. Finish: Seven layers– with proprietary nano ceramic impregnated commercial finish

6. Physical Property Performance Requirements:
  - a. Hardness: ASTM D 1037, Janka Ball
  - b. Flammability: ASTM E 648: Class I Interior Floor Finish
  - c. NFPA 255: Passes "life Safety Codes"
  - d. Smoke Density: ASTM E 622
  - e. Compressive Strength: ASTM D 3501
  - f. Slip Resistance: ASTM D 2394 Friction Coefficient
  - g. Abrasion Resistance: ASTM D1037
  - h. Moisture Content: ASTM D 4442 (varies based on distribution point)
  - i. Formaldehyde Emissions: CARB Compliant - <E0 standards
  - j. Lacey Act Compliance
- B. Installation Adhesive:
  1. One-part moisture-cured premium wood floor adhesive
  2. Nails or Staples:
    - a. 1-1/2 Inch (38 mm) Thick Subfloor: 2 inch nails or staples
    - b. 3/4 Inch (19 mm) Thick Subfloor: 1-1/2 inch nails or staples
    - c. 1 inch Thick Plywood Subfloor Over Concrete: 1-1/4 inch (32 mm) nails or staples
  3. Substitutions: None Permitted.

## **PART 3- EXECUTION**

### **3.01 EXAMINATION**

- A. Examine substrates prior to installation
- B. Verify that subfloor is clean, dry, and free of contaminants that would interfere with adhesive bond.
- C. Concrete installation:
  1. Test concrete floors for moisture content using a Calcium Chloride test or Tramex Moisture Encounter meter.
  2. Do not install flooring if vapor pressure exceeds 3 lbs per 1,000 sf (15 g per m<sup>2</sup>) in 24 hours, as under these conditions "urethane" adhesives tend to fail.
  3. In multiple story buildings, test each floor level
  4. Mark test location(s) on As-Built Drawings
- D. The subfloor moisture content is not to exceed 14% for plywood substrate.
  1. In multiple story buildings, test each floor level
  2. Mark test location(s) on As-Built Drawings.
- E. Verify that HVAC system is operating and maintaining occupancy level temperature and humidity conditions.
- F. If either of the above requires attendance, coordinate with responsible entity to correct unsatisfactory conditions.

### **3.02 PREPARATION**

- A. Acclimatization:
  1. Open all bundles, and let acclimate for a minimum of 72 hours.
  2. Fix the substrate to ensure bumps and depressions are less than 1/8" over 10 feet.

### **3.03 INSTALLATION**

- A. Install in accordance with manufacturer's installation instructions by either:
  1. nailing or stapling to substrate
  2. gluing to substrate
  3. nailing or stapling and gluing to substrate
  4. gluing t/g with cork underlayment
  5. Lay flooring in the direction(s)/pattern(s) as shown on Drawings.
  6. Inquire for Natural Bamboo® Installation Guidelines.
  7. Accessories: Install using methods appropriate to the accessory and flooring system.

### **3.04 CLEANING**

- A. Clean in accordance to Manufacturer's Maintenance Recommendations. Inquire for Natural Bamboo® maintenance guidelines.

### **3.05 PROTECTION**

- A. Remove visible adhesive and other surface blemishes using cleaner as recommended.
- B. Do not wash floor for at least five days following installation

- C. When the planks sufficiently seats (in no case less than five days), clean in accordance with USFloors written directions.
- D. After cleaning the flooring surface, it is necessary to protect the floor from mars, indentations, paint drippings, or other damage by either using building paper or by keeping traffic off the floors until the building is ready for occupancy.
- E. Do not use non-breathable sheet or film that could cause condensation to form. Maintain covering throughout remainder of construction period
- F. Should the floors become dirty or damaged prior to final acceptance by the Owner, they shall be repaired, recleaned, refinished, or replaced as required so that the Owner will receive floors ready for occupancy without additional cleaning before using.

### **3.06 OPERATIONS AND MAINTENANCE DOCUMENTS**

- A. Upon completion of floor installation the owner, attendants or individuals in charge responsible for upkeep of building are to follow care and maintenance instructions. Wait 48 hours after completion of installation and application of any finish before beginning maintenance program. Use finish manufacturer's maintenance instructions for bamboo floors, which have finish applied on site. Use USFloors maintenance instructions for prefinished bamboo floors that do not have extra finish applied on site.
- B. The General Contractor shall supply original copies of all flooring cleaning and maintenance information provided by USFloors. The Owner's maintenance personnel must receive this information upon completion of work.