

Natural Bamboo Strand Woven Natural with Natural-E™ oil finish

Technical Specifications

Description:	Solid strand woven bamboo flooring (compressed bamboo)
Species:	Mao Tzu Moso6™ Bamboo
Installation:	Glue-down, Nailed or Stapled
Sizes:	approx. 5 5/8" X 72" Micro-beveled edge – slight .2mm eased edge
Thickness:	12.7 mm
Finish:	Natural-E® Natural Organic Oil Finish Solvent free, 100% solid, Non-off gassing
Colors	4 standard prefinished colorways – Custom colors available
Strand Woven pressed:	Cold Pressed at 2000 US tons
VOC Emissions:	Proprietary phenol resin adhesive used in manufacturing, the formaldehyde emission exceeds E0 standard, no urea formaldehyde, no halogenated hydrocarbons, herbicides, heavy metals and any harmful emissions
Warranty:	15-year Class 34 – Lifetime structural
Dimensional Tolerance:	.0075% N/A w
Slip Resistance:	ADA and OSHA compliant
Moisture Content:	> 6 to < 9%
Certified Manufacturing:	ISO 9001 CARB2012 Lacey Act Compliance
Green Build Statement:	Natural Bamboo floors contribute to satisfying LEED credits for Rapidly Renewable Resources [MR] and Low Emitting Materials [EQ] under the LEED Rating System. The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes. Natural Bamboo® Strand Woven Solid can also contribute to attaining points within the Environmental Quality section of the LEED Rating Systems as it uses adhesives that meet the SCAQMD rule #1168 and it contains no added urea-formaldehyde, as required by LEED. The LEED (Leadership in Energy and Environmental Design) Green Building Rating System is the nationally accepted benchmark for the design, construction, and operation of high performance green buildings as administered by U.S. Green Building Council. USFloors is a member of the USGBC.