

## Homogeneous and Cork Colors™ vol. 1 Pro-pack Floor Primer

### Applications:

This primer is a premium, installer-grade primer used to improve adhesion on dry, dusty and porous substrates.

### Bonds To:

Bonds to and improves the bond of HENRY 331 Super Patch Latex Floor Patching Compound to concrete, poured-in-place gypsum subfloors, wood and wood underlayment's, radiant-heated subfloors where the surface temperature does not exceed 85°F (29°C), and wall surfaces including wood, plaster, drywall, and masonry.

- ◆ Improves adhesion on difficult substrates
- ◆ User-friendly with improved handling characteristics and working time
- ◆ Use as an additive for HENRY® 331 Super Patch Latex Floor Patching Compound ONLY

### SUBSTRATES:

The floor primer will bond as a primer to the substrates listed. Specific recommendations should come from the flooring manufacturer:

- ◆ Concrete
- ◆ Poured-in-place gypsum subfloors
- ◆ Wood and wood underlayment
- ◆ Radiant heated subfloors where the surface temperature does not exceed 85°F (29°C)
- ◆ Wall surfaces such as wood, plaster, drywall, and masonry

### INSTALLATION TIPS:

- ◆ Condition the area to be installed, adhesive, primer and flooring to 65°F (18°C) or above for 48 hours before, during, and for 48 hours after installation.
- ◆ Subfloor must be smooth, sound, dry, clean, and free of dirt, wax, polish, paint, and all other foreign matter, which may interfere with a good bond including curing agents and sealers. Concrete must be dry and free of excess alkali.
- ◆ Apply with a short nap paint roller or a coarse fiber brush. Do not allow puddles to form or remain on the surface.
- ◆ Use full strength.
- ◆ Allow to dry completely, approximately 30 minutes or more.
- ◆ Clean tools with water before material dries.

### Coverage:

Apply with brush or roller

300-450 sq. ft./gal

(33-50 sq. yd./gal.)

### Warranty:

USFloors Inc. warrants that the Pro-pack Floor Primer will not break down or lose its cohesive strength due to manufacturing or formulation defects for one year subject to certain exclusions and limitations set forth in the warranty, if used for its stated purpose and applied in accordance with the stated instructions.

### Warnings:

Carefully read and follow all cautions and warnings on the product label. Refer to the Material Safety Data Sheet for additional product information.

**Tech Support:** 1.706.733.6120 or toll free 800.404.2675